

M880 ARES2



Compact and rugged

ARES2 has been designed to be extremely robust and at the same time light and ergonomic. It is equipped with a practical clip for quick attachment to the belt. Fully customizable, it can be configured with buttons, toggle switches, rotary switches and potentiometers.

Technical data

Dimensions (L.W.A.)	143 x 80 x 143 mm / 5.63 x 3.15 x 5.63 in	
Weight (battery included)	700 g / 1,54 lb	
Max number of ON/OFF commands	32	
Max number of analog commands (optional)	4	
Range	100 m / 330 ft	
Casing material	Charged Nylon UL94 HB	
Battery	NiMh 3,6V - 2,2 Ah	
Autonomy at 20°C with charged battery in continuous service	≈ 25 hours	
	STOP	PLe Cat.4/SIL3
UMFS protection	JOYSTICK	PLd Cat.3/SIL3
	SELECTOR LEVER - BUTTON	PLc Cat.2/SIL2
Operating frequency 1	I.S.M. Band 433.050-434.790 MHz 69 ch.	
Operating frequency 2	I.S.M. 434.040-434.790 MHz 30 ch.	
Operating frequency 3	2,4 GHz, 38 ch.	
Operating frequency 4	I.S.M. Band 863.100-869.850 MHz 32 ch.	
Operating frequency 5	Band 915.200-927.800 MHz 64 ch.	
Operating temperature	-25°C +55°C / -13°F +133°F	
Degree of protection	IP 65	

Details

	STATUS LEDS Signaling operating status, battery charge level and anomaly messages.
	PIN CODE Access PIN code can be programmed to restrict the use to authorized personnel.
	STOP Highest level of safety according to international standards.
	MOVEMENT AND SELECTION Wide range of switches, push buttons, rotary switches and potentiometers.
	CLIP Durable clip for belt passage.
	BATTERY CHARGER BATTERIES Fast charger and extractable rechargeable NiMh batteries for extra long duration.

Functions

Pull/Release (considered with signaling Led), Gas +/-, Engine on/off. Optional function: PTO, intermittent brake release, emergency call.