

M880 KRON



Robust and innovative

KRON is designed for applications requiring up to 4 monoaxial joysticks. It can also be equipped with switches, buttons and potentiometers. Equipped with a practical clip for quick attachment to the belt, KRON will surprise you in terms of practicality and intuitive handling thanks to the design of its handle, which will make every work situation comfortable. Large side spaces are available for auxiliary controls.

Technical data

Dimensions (L.W.A.)	180 x 107 x 160 mm / 7.08 x 4.21 x 6.30 in
Weight (battery included)	900 g max / 1,98 lb
Max number of ON/OFF commands	56
Max number of analog commands (optional)	16
Max number of single-axis joysticks	4
Range	100 m / 330 ft
Casing material	Charged Nylon UL94 HB
Battery	NiMH 3,6V - 2,2 Ah
Autonomy at 20°C with charged battery in continuous service	≈ 22 hours
STOP	PLe Cat.4/SIL3
UMFS protection JOYSTICK	PLd Cat.3/SIL3
SELECTOR LEVER - BUTTON	PLc Cat.2/SIL2
Operating frequency 1	I.S.M. Band 433.050-434.790 MHz 69 ch.
Operating frequency 2	I.S.M. 434.040-434.790 MHz 30 ch.
Operating frequency 3	2,4 GHz, 38 ch.
Operating frequency 4	I.S.M. Band 863.100-869.850 MHz 32 ch.
Operating frequency 5	Band 915.200-927.800 MHz 64 ch.
Operating and storage temperature	-25°C +55°C / -13°F +133°F
Degree of protection	IP 65

Details

	STATUS LEDS Signaling operating status, battery charge level and anomaly messages.
	PIN CODE Access PIN code can be programmed to restrict the use to authorized personnel.
	STOP Highest level of safety according to international standards.
	MULTIAXIS JOYSTICKS Tested for 15.000.000 operations; long stroke lever with +/-40° tilting angle.
	ERGONOMIC BELTS Comfortable support belts.
	CLIP Durable clip for belt passage.
	BATTERY CHARGER BATTERIES Fast charger and extractable rechargeable NiMh batteries for extra long duration.

Options

Truck cranes retrofit kit, Tilt-Sensor, Serial Cable, MTRS, Kapta, Backlit transmitter panel.