


# M880 THOR2 W



**WIRED**

## Strong and complete

This CAN wired control represents the perfect synthesis of efficiency, ergonomics and high-degree customization. Robust and lightweight, it's an ideal mix of design and functionality that puts it at the top of its category. It's configurable with up to 9 monoaxial joysticks or 4 biaxial joysticks on the main panel, it has large lateral spaces for auxiliary controls.

THOR2 W can also integrate the 4.3" color graphic display or the 3.5" monochrome display. It's available with connectors M12, Deutsch 8-poles or circular Amphenol 18-poles. The emergency mushroom on the control unit can be used as "EMERGENCY STOP" if properly integrated with the emergency circuits of the machine (Maximum 2A, 30VDC).

## Technical data

Dimensions (L.W.A.)	295 x 180 x 160 mm / 11.61 x 7.08 x 6.30 in
Weight	2300 g / 5,07 lb max
Max number of ON/OFF commands	56
Max number of analog commands (optional)	16
Max number of single-axis joysticks	9
Max number of dual-axis joysticks	4
Casing material	Charged Nylon UL94 HB
Color graphic display (optional)	4,3"
Monochromatic display (optional)	3,5"
Operating temperature	-25°C +55°C / -13°F +133°F
Degree of protection	IP 65

## Details

	<b>STATUS LEDS</b> Signaling operating status, battery charge level and anomaly messages.
	<b>PIN CODE</b> Access PIN code can be programmed to restrict the use to authorized personnel.
	<b>STOP</b> Highest level of safety according to international standards.
	<b>MULTIAXIS JOYSTICKS</b> Tested for 15.000.000 operations; long stroke lever with +/-40° tilting angle.
	<b>ERGONOMIC BELTS</b> Comfortable support belts.
	<b>BATTERY CHARGER BATTERIES</b> Fast charger and extractable rechargeable NiMh batteries for extra long duration.

## Options

Truck cranes retrofit kit, Tilt-Sensor, Serial Cable, MTRS, Kapta, Twin B, Backlit transmitter panel.